BBA piston pump



Type: PT 90 E

6" electric driven on baseframe



General:

Cost of operation is one of the biggest concerns contractors have regarding their equipment. The BBA piston pump for well pointing, series PT is the solution.

Extremely efficient and packed with user benefits, the PT pumps are capable of operating for very long periods of time on a small amount of fuel. Plus, the pumps provide high air handling necessary on the toughest well point and sock applications.

The pump and motor are enclosed in the robust galvanized stackable frame, which protects the pump unit on working site. During transport the frames can be loaded 2 piece above each other. The PT series are self-priming, positive displacement piston pumps. Because of its efficient design, the pump is capable of operating with very low energy costs, dramatically reducing operational costs. The pumps also are environmentally friendly, sporting a double sealing piston rod which prevents any oil from entering the environment.

Applications:

This high efficient pump system is used for well point dewatering, under drain sock dewatering, filtered water transfers and remediation and reclamation.

Technical specifications:

1

5

Piston pump:

type flow max head max suction lift max cylinder size req. power pump speed suction side discharge side

: double acting 90 m3/h 1 20 m 9,2 m 175 mm 6.0 kW : 62 strokes/min : : 6" V-part incl. stone catcher : 6" V-part

Materials:

pump casing cylinder liner piston cup piston rod shaft seal O rings

: cast iron : stainless steel AISI 316 : leather : stainless steel AISI 316 : gland packaging : NBR

BBA Pumps BV

Edisonstraat 12, 7006 RD P.O. Box 498, 7000 AL Doetinchem

Pumps for results Tel. (+31) 314 36 84 36 Fax. (+31) 314 37 84 03

www.bbapumps.com info@bbapumps.com

1800 PUMP RENTAL

nationalpump.com.au | sales@nationalpump.com.au



BBA piston pump

Type: PT 90 E

6" electric driven on baseframe

Electric drive:

motor power	:7,5 kW
voltage	: 400/690 Volt
speed	: 1480 rpm - 4-pole
motor execution	: IM 1001, IP 55, ISO F
start	: start delta switch with
	thermic protection
assembly	: galvanized base frame
	with central lifting
	hook and protection cover
	over the electric motor
noise level	:55 dBa at 10 m


Dimensions:

l x w x h weight : 2000 x 890 x 1145 mm : 1140 kg



Special features:





Simple exchanges cylinder liners, saves maintenance costs


Pump casing provided with cleaning covers, for simple and easy cleaning of cylinder liners and changing gland packaging

Easy to operate by everybody

Designed for life!



BBA Pumps BV Edisonstraat 12, 7006 RD P.O. Box 498, 7000 AL Doetinchem



Pumps for results Tel. (+31) 314 36 84 36 Fax. (+31) 314 37 84 03

www.bbapumps.com info@bbapumps.com

1800 PUMP RENTAL nationalpump.com.au | sales@nationalpump.com.au



