



## DIESEL/ELECTRIC DRIVEN SELF-PRIMING DEWATERING PUMP 200-40-150 CORNELL



The NPE 200-40-150HP is a robust, reliable and high performance pumping solution capable of handling the harshest of conditions with ease.

Renowned for it's durability and performance, the NPE 200-40-150HP pump is the right choice when you need a solution that will deliver day-in and day-out.

### ENGINE SPECIFICATIONS

Engine	Cummins QSB6.7
--------	----------------

### PUMP SPECIFICATIONS

Min Flow	56 L/s
Max Flow	236 L/s
Discharge Size	200 mm
Suction Size	200 mm
Solids Handling	85 mm
Max Speed	1900 RPM
Shut-off Head	69 m
BEP Head	46 m
BEP Flow	193 L/s
BEP Efficiency	77%

### KEY FEATURES

- Heavy-duty construction
- Lower maintenance costs
- Super fast and strong
- Stainless steel shaft sleeve
- Dual Axle Mine Spec Trailer
- Powered by Cummins Engine
- Corrosion and abrasion resistant impeller

### MATERIALS OF CONSTRUCTION

Wear Ring	Cast Iron
Impeller	CA6NM
Volute	Ductile Iron
Shaft	17-4 PH Stainless Steel
Shaft Sleeve	416 Stainless Steel
Backplate	Ductile Iron
Mechanical Seal	Tungsten Carbide vs. Silicon Carbide
O-Rings	Silicon Carbide
Bearing Frame	F18DB Cast Iron





## DIESEL/ELECTRIC DRIVEN SELF-PRIMING DEWATERING PUMP 200-40-150 CORNELL

